

US009270766B2

(12) United States Patent

Rovniaguin et al.

(54) METHODS FOR IDENTIFYING NETWORK TRAFFIC CHARACTERISTICS TO CORRELATE AND MANAGE ONE OR MORE SUBSEQUENT FLOWS AND DEVICES THEREOF

(75) Inventors: **Dmitry Rovniaguin**, Rishon Le Zion

(IL); **Ephraim Dan**, Yad-Binyamin (IL); **Ron Talmor**, Sunnyvale, CA (US)

(73) Assignee: F5 Networks, Inc., Seattle, WA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 13/341,360

(22) Filed: Dec. 30, 2011

(65) **Prior Publication Data**

US 2013/0173779 A1 Jul. 4, 2013

(51) Int. Cl.

G06F 17/30 (2006.01) **H04L 29/08** (2006.01) **H04L 29/06** (2006.01)

(52) U.S. Cl.

CPC H04L 67/22 (2013.01); H04L 63/1408 (2013.01); H04L 63/20 (2013.01); H04L 67/02 (2013.01); H04L 67/2819 (2013.01)

(58) Field of Classification Search

USPC 370/235; 707/999.01; 709/223–225; 726/22, 23

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,950,735 A	4/1976	Patel
4,644,532 A	2/1987	George et al.
4,897,781 A	1/1990	Chang et al.
4,965,772 A	10/1990	Daniel et al.
5,023,826 A	6/1991	Patel

(10) Patent No.: US 9,270,766 B2

(45) **Date of Patent:** Feb. 23, 2016

5.053.953 A	10/1991	Patel		
5.167.024 A		Smith et al.		
5,299,312 A	3/1994	Rocco, Jr.		
5,327,529 A		Fults et al.		
5,367,635 A	11/1994	Bauer et al.		
5,371,852 A	12/1994	Attanasio et al.		
	(Continued)			

FOREIGN PATENT DOCUMENTS

EP	0744850 A2	11/1996
EP	2244418 A1	10/2010
	(Cont	inued)

OTHER PUBLICATIONS

"Testing for Cross site scripting". In The Open Web Application Security Project (OWASP) [online]. Feb. 24, 2011; [retrieved on May 2, 2013]. Retrieved from the Internet: .*">http://www.owasp.org/index.php/Testing_for_Cross_site_scripting>.*


(Continued)

Primary Examiner — Jason K. Gee Assistant Examiner — Zhimei Zhu (74) Attorney, Agent, or Firm — LeClairRyan, a Professional Corporation

(57) ABSTRACT

A method, non-transitory computer readable medium, and device that identifies network traffic characteristics to correlate and manage one or more subsequent flows includes transmitting a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the HTTP request. The HTTP request is transmitted to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server. An HTTP response to the HTTP request is received from the application server. An operation with respect to the HTTP response is performed.

18 Claims, 5 Drawing Sheets



US 9,270,766 B2 Page 2

(56)	References Cited	6,650,640 B1		Muller et al.
IIS	S. PATENT DOCUMENTS	6,650,641 B1 6,654,701 B2	11/2003	Albert et al. Hatlev
0.5	STREET BOCOMENTS	6,661,802 B1	12/2003	Homberg et al.
5,406,502 A	4/1995 Haramaty et al.	6,683,873 B1		Kwok et al.
5,475,857 A	12/1995 Dally	6,691,165 B1 6,694,517 B1		Bruck et al. James et al.
5,517,617 A 5,519,694 A	5/1996 Sathaye et al. 5/1996 Brewer et al.	6,708,187 B1	3/2004	
5,519,778 A	5/1996 Leighton et al.	6,718,380 B1	4/2004	Mohaban et al.
5,521,591 A	5/1996 Arora et al.	6,742,045 B1		Albert et al.
5,528,701 A	6/1996 Aref	6,751,663 B1 6,754,228 B1		Farrell et al. Ludwig
5,581,764 A 5,596,742 A	12/1996 Fitzgerald et al. 1/1997 Agarwal et al.	6,760,775 B1	7/2004	Anerousis et al.
5,606,665 A	2/1997 Yang et al.	6,772,219 B1		Shobatake
5,611,049 A	3/1997 Pitts	6,779,039 B1 6,781,986 B1		Bommareddy et al. Sabaa et al.
5,663,018 A 5,752,023 A	9/1997 Cummings et al. 5/1998 Choucri et al.	6,798,777 B1		Ferguson et al.
5,761,484 A	6/1998 Agarwal et al.	6,804,542 B1		Haartsen
5,768,423 A	6/1998 Aref et al.	6,816,901 B1 6,816,977 B2		Sitaraman et al. Brakmo et al.
5,774,660 A 5,790,554 A	6/1998 Brendel et al. 8/1998 Pitcher et al.	6,829,238 B2		Tokuyo et al.
5,802,052 A	9/1998 Venkataraman	6,868,082 B1	3/2005	Allen, Jr. et al.
5,812,550 A	9/1998 Sohn et al.	6,876,629 B2		Beshai et al.
5,825,772 A 5,832,283 A	10/1998 Dobbins et al.	6,876,654 B1 6,888,836 B1	4/2005 5/2005	Cherkasova
5,875,296 A	11/1998 Chou et al. 2/1999 Shi et al.	6,928,082 B2	8/2005	Liu et al.
5,892,914 A	4/1999 Pitts	6,947,985 B2		Hegli et al.
5,892,932 A	4/1999 Kim	6,950,434 B1 6,954,780 B2		Viswanath et al. Susai et al.
5,919,247 A 5,936,939 A	7/1999 Van Hoff et al. 8/1999 Des Jardins et al.	6,957,272 B2		Tallegas et al.
5,941,988 A	8/1999 Bhagwat et al.	6,959,394 B1	10/2005	Brickell et al.
5,946,690 A	8/1999 Pitts	6,975,592 B1		Seddigh et al.
5,949,885 A	9/1999 Leighton	6,986,040 B1 6,987,763 B2	1/2006	Kramer et al. Rochberger et al.
5,951,694 A 5,959,990 A	9/1999 Choquier et al. 9/1999 Frantz et al.	7,007,092 B2	2/2006	
5,974,460 A	10/1999 Maddalozzo, Jr. et al.	7,058,633 B1	6/2006	Gnagy et al.
5,983,281 A	11/1999 Ogle et al.	7,113,993 B1 7,133,944 B2		Cappiello et al. Song et al.
5,988,847 A 6,006,260 A	11/1999 McLaughlin et al. 12/1999 Barrick, Jr. et al.	7,139,792 B1		Mishra et al.
6,006,264 A	12/1999 Barrick, 31. et al.	7,185,359 B2	2/2007	Schmidt et al.
6,026,452 A	2/2000 Pitts	7,228,422 B2		Morioka et al.
6,028,857 A	2/2000 Poor	7,287,082 B1 7,295,827 B2		O'Toole, Jr. Liu et al.
6,051,169 A 6,078,956 A	4/2000 Brown et al. 6/2000 Bryant et al.	7,308,703 B2		Wright et al.
6,085,234 A	7/2000 Pitts et al.	7,308,709 B1		Brezak et al.
6,092,196 A	7/2000 Reiche	7,310,339 B1 7,319,696 B2		Powers et al. Inoue et al.
6,108,703 A 6,111,876 A	8/2000 Leighton et al. 8/2000 Frantz et al.	7,321,926 B1		Zhang et al.
6,128,279 A	10/2000 O'Neil et al.	7,333,999 B1		Njemanze
6,128,657 A	10/2000 Okanoya et al.	7,343,413 B2 7,349,391 B2		Gilde et al. Ben-Dor et al.
6,160,874 A 6,170,022 B1	12/2000 Dickerman et al. 1/2001 Linville et al.	7,349,391 B2 7,383,570 B2		Pinkas et al.
6,178,423 B1	1/2001 Envine et al.	7,398,552 B2		Pardee et al.
6,182,139 B1	1/2001 Brendel	7,433,962 B2		Janssen et al.
6,192,051 B1 6,233,612 B1	2/2001 Lipman et al. 5/2001 Fruchtman et al.	7,437,478 B2 7,454,480 B2		Yokota et al. Labio et al.
6,246,684 B1	6/2001 Chapman et al.	7,490,162 B1	2/2009	Masters
6,253,226 B1	6/2001 Chidambaran et al.	7,500,243 B2		Huetsch et al.
6,253,230 B1	6/2001 Couland et al.	7,500,269 B2 7,505,795 B1		Huotari et al. Lim et al.
6,263,368 B1 6,289,012 B1	7/2001 Martin 9/2001 Harrington et al.	7,516,492 B1		Nisbet et al.
6,298,380 B1	10/2001 Coile et al.	7,522,581 B2		Acharya et al.
6,327,622 B1	12/2001 Jindal et al.	7,526,541 B2 7,558,197 B1	4/2009 7/2009	Roese et al. Sindhu et al.
6,343,324 B1 6,347,339 B1	1/2002 Hubis et al. 2/2002 Morris et al.	7,580,971 B1		Gollapudi et al.
6,360,270 B1	3/2002 Cherkasova et al.	7,590,732 B2	9/2009	Rune
6,374,300 B2	4/2002 Masters	7,624,424 B2		Morita et al.
6,396,833 B1	5/2002 Zhang et al.	7,644,137 B2 7,668,166 B1		Bozak et al. Rekhter et al.
6,430,562 B1 6,434,081 B1	8/2002 Kardos et al. 8/2002 Johnson et al.	7,689,710 B2		Tang et al.
6,480,476 B1	11/2002 Willars	7,724,657 B2	5/2010	Rao et al.
6,484,261 B1	11/2002 Wiegel	7,725,093 B2		Sengupta et al.
6,490,624 B1	12/2002 Sampson et al.	7,778,187 B2 7,801,978 B1		Chaturvedi et al. Susai et al.
6,510,135 B1 6,510,458 B1	1/2003 Almulhem et al. 1/2003 Berstis et al.	7,801,978 B1 7,808,913 B2		Ansari et al.
6,519,643 B1	2/2003 Foulkes et al.	7,831,662 B2		Clark et al.
6,601,084 B1	7/2003 Bhaskaran et al.	7,908,314 B2	3/2011	Yamaguchi et al.
6,636,503 B1	10/2003 Shiran et al.	7,925,908 B2	4/2011	
6,636,894 B1	10/2003 Short et al.	7,930,365 B2	4/2011	Dixit et al.

US 9,270,766 B2 Page 3

(56)	Referen	ces Cited	2004/0151186 A1		Akama
U.S	S. PATENT	DOCUMENTS	2004/0192312 A1 2004/0264472 A1	12/2004	Li et al. Oliver et al.
			2004/0264481 A1		Darling et al.
7,933,946 B2		Livshits et al 709/200	2004/0267920 A1 2004/0267948 A1		Hydrie et al. Oliver et al.
7,945,908 B1 7,984,141 B2		Waldspurger et al. Gupta et al.	2004/0268358 A1		Darling et al.
8,103,781 B1		Wu et al.	2005/0004887 A1	1/2005	Igakura et al.
8,130,650 B2	2 3/2012	Allen, Jr. et al.	2005/0021736 A1*		Carusi et al 709/224
8,189,567 B2		Kavanagh et al.	2005/0027869 A1 2005/0044213 A1*		Johnson Kobayashi et al 709/224
8,199,757 B2 8,205,246 B2		Pani et al. Shatzkamer et al.	2005/0052440 A1		Kim et al.
8,239,954 B2		Wobber et al.	2005/0055435 A1		Gbadegesin et al.
8,274,895 B2		Rahman et al.	2005/0078604 A1 2005/0122977 A1	4/2005	Yım Lieberman
8,321,908 B2 8,351,333 B2		Gai et al. Rao et al.	2005/0154837 A1		Keohane et al.
8,380,854 B2			2005/0187866 A1	8/2005	Lee
8,417,817 B1	4/2013	Jacobs	2005/0188220 A1		Nilsson et al.
8,447,871 B1			2005/0188423 A1* 2005/0198310 A1		Motsinger et al 726/22 Kim et al.
8,447,970 B2 8,464,265 B2		Klein et al. Worley	2005/0190310 A1 2005/0262238 A1		Reeves et al.
8,468,267 B2			2006/0031520 A1		Bedekar et al.
8,539,224 B2		Henderson et al.	2006/0059267 A1 2006/0077902 A1		Cugi et al. Kannan et al.
8,566,474 B2 8,578,050 B2		Kanode et al. Craig et al.	2006/0095573 A1*		Carle H04L 63/02
8,606,921 B2		Vasquez et al.			709/227
8,615,022 B2		Harrison et al.	2006/0112176 A1		Liu et al.
8,646,067 B2	2 2/2014	Agarwal et al.	2006/0112272 A1 2006/0129684 A1	6/2006	Morioka et al.
8,665,868 B2 8,701,179 B1		Penno et al.	2006/0125004 A1	6/2006	
8,725,836 B2		Lowery et al.	2006/0156416 A1		Huotari et al.
8,726,338 B2	2 5/2014	Narayanaswamy et al.	2006/0161577 A1		Kulkarni et al.
8,737,304 B2		Karuturi et al.	2006/0171365 A1 2006/0209853 A1		Borella Hidaka et al.
8,788,665 B2 8,804,504 B1		Gilde et al.	2006/0230148 A1		Forecast et al.
8,819,109 B1		Krishnamurthy et al.	2006/0233106 A1		Achlioptas et al.
8,819,419 B2	8/2014	Carlson et al.	2006/0242300 A1		Yumoto et al.
8,819,768 B1		Koeten et al.	2007/0006293 A1 2007/0016662 A1		Balakrishnan et al. Desai et al.
8,830,874 B2 8,873,753 B2		Cho et al. Parker	2007/0058670 A1		Konduru et al.
8,875,274 B2		Montemurro et al.	2007/0064661 A1		Sood et al.
8,886,981 B1		Baumann et al.	2007/0083646 A1 2007/0088822 A1		Miller et al. Coile et al.
8,908,545 B1 8,954,080 B2		Chen et al. Janakiriman et al.	2007/0008822 A1 2007/0106796 A1		Kudo et al.
9,037,166 B2		de Wit et al.	2007/0107048 A1		Halls et al.
9,077,554 B1	7/2015	Szabo	2007/0118879 A1	5/2007	
9,083,760 B1		Hughes et al.	2007/0124806 A1* 2007/0136312 A1*		Shulman et al
2001/0009554 A1 2001/0023442 A1		Katseff et al. Masters	2007/0174491 A1	7/2007	
2002/0010783 A1		Primak et al.	2007/0220598 A1	9/2007	
2002/0032777 A1		Kawata et al.	2007/0233809 A1 2007/0297410 A1		Brownell et al. Yoon et al.
2002/0049842 A1 2002/0059428 A1		Huetsch et al. Susai et al.	2007/0297410 A1 2007/0297551 A1	12/2007	
2002/0033428 A1 2002/0083067 A1		Tamayo et al.	2008/0025297 A1		
2002/0112061 A1	8/2002	Shih et al.	2008/0034136 A1		Ulenas
2002/0138615 A1		Schmeling 709/225	2008/0072303 A1 2008/0120370 A1	3/2008 5/2008	Chan et al.
2002/0161913 A1 2002/0194342 A1		Gonzalez et al. Lu et al.	2008/0133518 A1		Kapoor et al.
2002/0198993 A1		Cudd et al.	2008/0134311 A1		Medvinsky et al.
2003/0037070 A1		Marston	2008/0148340 A1 2008/0159145 A1		Powell et al. Muthukrishnan et al.
2003/0046291 A1 2003/0065951 A1		Fascenda Igeta et al.	2008/0178278 A1*		Grinstein et al 726/12
2003/0003931 A1 2003/0069918 A1		Lu et al.	2008/0201599 A1	8/2008	Ferraiolo et al.
2003/0069974 A1	4/2003	Lu et al.	2008/0205613 A1	8/2008	
2003/0070069 A1		Belapurkar et al.	2008/0222646 A1 2008/0225710 A1		Sigal et al. Raja et al.
2003/0086415 A1 2003/0105983 A1		Bernhard et al. Brakimo et al.	2008/0229415 A1		Kapoor et al.
2003/0103983 A1 2003/0108052 A1		Inoue et al.	2008/0253395 A1	10/2008	Pandya
2003/0128708 A1		Inoue et al.	2008/0256224 A1		Kaji et al.
2003/0145062 A1		Sharma et al. 713/201	2008/0275843 A1* 2008/0288661 A1	11/2008	Lal et al 707/3
2003/0145233 A1 2003/0163576 A1		Poletto et al 713/201 Janssen et al.	2008/0301760 A1	12/2008	
2003/0225485 A1	1 12/2003	Fritz et al.	2009/0028337 A1	1/2009	Balabine et al.
2004/0003287 A1		Zissimopoulos et al.	2009/0049230 A1		Pandya
2004/0072569 A1		Omae et al.	2009/0070617 A1		Arimilli et al.
2004/0103283 A1 2004/0111523 A1		Hornak Hall et al.	2009/0077619 A1 2009/0094610 A1	3/2009 4/2009	Boyce Sukirya
2004/0111621 A1		Himberger et al.	2009/0119504 A1	5/2009	van Os et al.
2004/0117493 A1		Bazot et al.	2009/0125496 A1*	5/2009	Wexler et al 707/4

(56)	Referer	ices Cited		WO WO	WO 99/06913 WO 99/10858	2/1999 3/1999
	IIS PATENT	DOCUMENTS		WO	WO 99/10838 WO 99/39373	8/1999
	O.S. TATENT	DOCOMENTS		WO	WO 99/64967	12/1999
2009/0125	5532 A1* 5/2009	Wexler et al	. 707/100	WO	WO 00/04422	1/2000
2009/0125		Shim et al.		WO	WO 00/04458	1/2000
2009/0138		Moll et al.			OTHER PU	BLICATIONS
2009/0141		Boyen et al.			OTHERTO	BEIGHHOLG
2009/0196		Fellman et al. He et al.		"A Process	s for Selective Routing	g of Servlet Content to Transcoding
2009/0228 2009/0283		Aull et al.		Modules,"	Research Disclosure	422124, Jun. 1999, pp. 889-890,
2009/0296		Ryu et al.		IBM Corp	oration.	
2009/0300		Kamath et al.		F5 Networ	ks, Inc., "BIG-IP Cor	ntroller with Exclusive OneConnect
2010/0011						vides a Breakthrough System for
2010/0017		Huang et al.				Performance," Press Release, May
2010/0023		Pedersen et al.			pages, Las Vegas, Nev	
2010/0071 2010/0115		Novak et al. Bataineh et al.				on Layer Processing (ALP)," 2003- CN-5000E/5500E, Foxit Software
2010/0112		Huang et al.		Company.	100-100, Chapter 3,	en-3000E/3300E, Toxit Boltware
2010/0150		Viger et al.		1 2	al., "Hypertext Trans	fer Protocol—HTTP/1.1," Network
2010/0165	5877 A1 7/2010	Shukla et al.			roup, RFC: 2068, Jar	
2010/0242		Harris et al.		Fielding et	al., "Hypertext Trans	fer Protocol—HTTP/1.1," Network
2010/0251		Kroeselberg et al.			Group, RFC: 2616, J	un. 1999, pp. 1-176, The Internet
2010/0278 2010/0322		Karsten et al. Shetty et al.		Society.	1 #D 1 E 1 D	
2010/0322		Muthiah et al.		•	•	etection Gateways for Congestion
2011/0040		Garrett et al.				2, IEEE/ACM Transactions on Net-
2011/0047		Mahaffey et al.		working, C		vy nymn yn aantant daliyaar linaa?
2011/0066		Susai et al.				w pump up content-delivery lines," 2001, 1 page, Las Vegas, Nevada.
2011/0153		Rajan et al.				s Part 5—Protocol Transition, Con-
2011/0154 2011/0173		Thakur et al. Bakke et al.				1 S4U2P," Jul. 18, 2007, 21 pages,
2011/01/2		Yu et al.				/blogs/ken/archive/2007/07/8460.
		Soukal et al	. 707/709	aspx.	F	
2011/0246		Accpadi et al.			pplet/HTML Authent	ication Process With Single Sign-
2011/0273		Hsu et al.				.28, Jan. 2000, pp. 163-164, IBM
		Prince et al	. 709/226	Corporatio		
2011/0321 2012/0016		Mwangi et al. Nakamura et al.				etscaler Defense," 2005, PowerPoint
2012/0039		Latif et al.			on, slides 1-12, Citrix	
2012/0041		Vasquez et al.				hentication," The Ultimate Windows
2012/0063		Pignataro et al.				tor's Guide, 2003, 2 pages, Figure
	5489 A1* 3/2012	Ozaki et al	. 713/151			nal, Boston, Massachusetts.
2012/0101		Raleigh et al.				s Extensions," Microsoft TechNet, http://technet.microsoft.com/en-us/
2012/0191 2012/0311		Nas et al. Morgan			38207, Microsoft Co	
2012/0317						d Load Balancing," Technical Brief,
2013/0029		Berionne et al.			pp. 1-9, F5 Networks	
2013/0091		Christie et al.				on Guide for Local Traffic Manage-
2013/0198		Oran et al.				006, version 9.2.2, 406 pgs.
2013/0336		Barush et al.		Internation	al Search Report for I	nternational Patent Application No.
2014/0025 2014/0040		Szabo et al. Hsu et al.		PCT/US20	012/071648 (May 27,	2013).
2014/0095		Knowles et al.		, ,	,	on the Schemes for Detecting and
2014/0269		Dankberg et al.				ng Attacks", IEEE, Computer Soci-
2014/0317		Carlson et al.				ice on Distributed Computing Sys-
					shops (ICDCSW'07),	
	FOREIGN PATE	NT DOCUMENTS				scripting", OWASP Testing Guide
					g for Cross site s	11, pp. 1-5, (www.owasp.org/index.
GB	2448071 A	1/2008				the Written Opinion, for Interna-
WO	WO 91/14326	9/1991				CT/US2011/058469, Date of Mail-
WO WO	WO 95/05712 WO 97/09805	2/1995 3/1997		ing: Mar. 1	* *	CI, CDEOTH ODO 109, Date of White-
WO	WO 97/45800	3/1997 12/1997			,	
wo	WO 99/05829	2/1999		* cited by	examiner	
					-	




FIG. 1





FIG. 2







FIG. 4



METHODS FOR IDENTIFYING NETWORK TRAFFIC CHARACTERISTICS TO CORRELATE AND MANAGE ONE OR MORE SUBSEQUENT FLOWS AND DEVICES THEREOF

FIELD

This technology relates to methods for identifying network traffic characteristics to correlate and manage one or more 10 subsequent flows and devices thereof.

BACKGROUND

As enterprise customers deploy more web-based database applications, IT administrators face several challenges for correlating and managing subsequent flows. For example, IT administrators would like to provide a data access audit trail which is not always possible. Additionally, IT administrators would like to be able to monitor and effectively alert or 20 terminate a user session deemed to be misbehaving based on a data or other access policy. Further, IT administrators would like to secure both application and database environments from threats, such as SQL injection and cross-site scripting attacks.

SUMMARY

A method for identifying network traffic characteristics to correlate and manage one or more subsequent flows includes 30 transmitting, by a traffic management computing device, a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the 35 HTTP request. The HTTP request is transmitted, by the traffic management computing device, to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server. An HTTP response to the HTTP request is received, by the traffic management com- 40 puting device, from the application server. An operation with respect to the HTTP response is performed, by the traffic management computing device, after transmitting a monitoring response message to end the correlation associated with the HTTP request in response to the monitoring request.

A non-transitory computer readable medium having stored thereon instructions for identifying network traffic characteristics to correlate and manage one or more subsequent flows comprising machine executable code which when executed by at least one processor, causes the processor to perform steps including transmitting a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the HTTP request. The HTTP request is transmitted to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server. An HTTP response to the HTTP request is received from the application server. An operation with respect to the HTTP response is performed.

A traffic management computing device includes a memory coupled to one or more processors which are configured to execute programmed instructions stored in the memory including transmitting a monitoring request comprising one or more attributes extracted from an HTTP 65 request received from a client computing device and a timestamp to a monitoring server to correlate one or more subse-

2

quent flows associated with the HTTP request. The HTTP request is transmitted to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server. An HTTP response to the HTTP request is received from the application server. An operation with respect to the HTTP response is performed

This technology provides a number of advantages including providing effective methods, non-transitory computer readable medium, and devices that identify network traffic characteristics to correlate and manage one or more subsequent flows. With this technology, access audit trails can be generated that are granular at the data level and also tie in attributes from the web application layer. Additionally, this technology can monitor and effectively alert or terminate a user session deemed to be misbehaving based on a data access policy. Further, this technology helps to secure both application and database environments from threats, such as SQL injection and cross-site scripting attacks.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an environment with an exemplary traffic management computing device that identifies network traffic characteristics to correlate and manage one or more subsequent flows;

FIGS. 2 and 3 are flow and functional diagrams of a method for identifying network traffic characteristics to correlate and monitor one or more subsequent flows to generate an audit trail; and

FIGS. 4 and 5 are flow and functional diagrams of a method for identifying network traffic characteristics to correlate and manage access to one or more subsequent flows.

DETAILED DESCRIPTION

An environment 10 with an exemplary traffic management computing device that identifies network traffic characteristics to correlate and manage one or more subsequent flows is illustrated in FIG. 1. The environment 10 includes a traffic management computing device 12, a plurality of client computing devices 14(1)-14(n), a database monitoring server 16, a web application server 18, and data servers 20(1)-20(n) which are all coupled together by one or more communication networks 21(1)-21(4), although this environment can 45 include other numbers and types of systems, devices, components, and elements in other configurations. This technology provides a number of advantages including providing effective methods, non-transitory computer readable medium, and devices that identify network traffic characteristics to correlate and manage one or more subsequent flows, such as request and/or response flows.

The traffic management computing device 12 provides a number of functions as illustrated and described with the examples herein including identifying network traffic characteristics to correlate and manage one or more subsequent flows, although other numbers and types of systems can be used and other numbers and types of functions can be performed. In this example, the traffic management computing device 12 includes a central processing unit (CPU) or proces-60 sor 22, a memory 24, and an interface system 26 which are coupled together by a bus or other link, although other numbers and types of systems, devices, components, and elements in other configurations production data storage device 16, and a backup data storage device 18 and locations can be used. The processor 22 executes a program of stored instructions for one or more aspects of the present technology as described and illustrated by way of the examples herein, although other

types and numbers of processing devices and logic could be used and the processor 22 could execute other numbers and types of programmed instructions.

The memory 24 stores these programmed instructions for one or more aspects of the present technology as described 5 and illustrated herein, although some or all of the programmed instructions could be stored and executed elsewhere. A variety of different types of memory storage devices, such as a random access memory (RAM) or a read only memory (ROM) in the system or a floppy disk, hard disk, 10 CD ROM, DVD ROM, or other computer readable medium which is read from and written to by a magnetic, optical, or other reading and writing system that is coupled to the processor 22, can be used for the memory 24.

In this example, the interface system 26 in the traffic man- 15 agement computing device 12 is used to operatively couple and communicate between the traffic management computing device 12 and the plurality of client computing devices 14(1)-14(n), the database monitoring server 16, and the web application server 18, which are all coupled together by one or 20 more communication networks 21(1), 21(2), and 21(4), although other types and numbers of communication networks or systems with other types and numbers of connections and configurations to other devices and elements, such as communication network 21(3) to communicate with data 25 servers 20(1)-20(n) could be used. In this illustrative example, application, web application server 18 is coupled to data servers 20(1)-20(n) via communication network 20(3). Additionally, by way of example only, the one or more the communications networks can use TCP/IP over Ethernet and 30 industry-standard protocols, including NFS, CIFS, SOAP, XML, LDAP, and SNMP, although other types and numbers of communication networks, such as a direct connection, a local area network, a wide area network, modems and phone lines, e-mail, and wireless communication technology, each 35 having their own communications protocols, can be used. In the exemplary environment 10 shown in FIG. 1, three communication networks 21(1)-21(4) are illustrated, although other numbers and types could be used.

The client computing devices 14(1)-14(n), the database 40 monitoring server 16, the web application server 18, and the data servers 20(1)-20(n) each may include a central processing unit (CPU) or processor, a memory, and an interface or I/O system, which are coupled together by a bus or other link, although each could comprise other numbers and types of 45 elements and components, such as configured control logic to execute one or more aspects of this technology. Each of the client computing devices 14(1)-14(n) may submit an HTTP request for data or operations from the web application server 18 through the traffic management computing device 12 and 50 may receive HTTP responses, although other numbers and types of requests and responses can be transmitted and received and other types and numbers of functions could be performed.

The database monitoring server 16 may interact with the 55 traffic management device 12 to receive one or more attributes extracted from the HTTP request along with a timestamp and may use the attributes and timestamp to correlate one or more subsequent flows associated with the HTTP request to one or more of the data servers 20(1)-20(n), 60 although other numbers and types of functions can be performed.

The web application server 18 may receive and process the one or more HTTP requests or other requests from one or more of the client computing devices 14(1)-14(n) to execute 65 one or more SQL queries or requests to obtain responsive data or other information from one or more of the data servers

4

20(1)-20(n), although other numbers and types of functions can be performed. Each of the data servers 20(1)-20(n) store content, such as files and directories, in relational databases and perform other operations, although other numbers and types of servers or other computing device which could have other numbers and types of functions and/or store other data could be used.

Although an example of the traffic management computing device 12, the plurality of client computing devices 14(1)-14 (n), the database monitoring server 16, the web application server 18, and the data servers 20(1)-20(n) are described herein, other types and numbers of devices could be used and each of these devices could be implemented in other configurations and manners on one or more of any suitable computer system or computing device. It is to be understood that the devices and systems of the examples described herein are for exemplary purposes, as many variations of the specific hardware and software used to implement the examples are possible, as will be appreciated by those skilled in the relevant art(s).

Furthermore, each of the systems of the examples may be conveniently implemented using one or more general purpose computer systems, microprocessors, digital signal processors, and micro-controllers, programmed according to the teachings of the examples, as described and illustrated herein, and as will be appreciated by those ordinary skill in the art.

In addition, two or more computing systems or devices can be substituted for any one of the systems in any embodiment of the examples. Accordingly, principles and advantages of distributed processing, such as redundancy and replication also can be implemented, as desired, to increase the robustness and performance of the devices and systems of the examples. The examples may also be implemented on computer system or systems that extend across any suitable network using any suitable interface mechanisms and communications technologies, including by way of example only telecommunications in any suitable form (e.g., voice and modem), wireless communications media, wireless communications networks, cellular communications networks, G3 communications networks, Public Switched Telephone Network (PSTNs), Packet Data Networks (PDNs), the Internet, intranets, and combinations thereof.

The examples may also be embodied as a non-transitory computer readable medium having instructions stored thereon for one or more aspects of the present technology as described and illustrated by way of the examples herein, as described herein, which when executed by a processor, cause the processor to carry out the steps necessary to implement the methods of the examples, as described and illustrated herein.

An exemplary method for identifying network traffic characteristics to correlate and monitor one or more subsequent flows to generate an audit trail will now be described with reference to FIGS. 1-3. In step 100, the traffic management computing device 12 monitors for when one of the client computing devices 14(1)-14(n) performs a login request and submits a login form containing username or other login identifier, although other manners for monitoring a login, such as the traffic management computing device 12 providing an initial login page, could be used.

In step 102, the traffic management computing device 12 determines whether a received user request, such as an HTTP request by way of example only, with a username or other login credentials can be associated with one of the client computing devices 14(1)-14(n), although other types of requests from other types of devices could be received. If in step 102, the traffic management computing device 12 can not

associate the received user request with the username or other login credentials with one of the client computing devices 14(1)-14(n), then the No branch is taken to step 104.

In step 104, the traffic management computing device 12 determines whether this exemplary method should end, such 5 as when the user at the one of the client computing devices 14(1)-14(n) logs out or stops browsing by way of example only, although other manners for determining when this method should end can be used. If in step 104 the traffic management computing device 12 determines this exemplary method should end, then the Yes branch is taken to step 106 where this exemplary method ends. If in step 104 the traffic management computing device 12 determines this exemplary method should not end, then the No branch is taken back to step 102 as described earlier.

If back in step 102, the traffic management computing device 12 can associate a received user request with a username or other login credentials with one of the client computing devices 14(1)-14(n), then the Yes branch is taken to step 108. For illustration purposes in FIG. 3 for this particular 20 example, the user request is provided by the client computing device 14(1), although other types of devices could provide the request.

In step 108, the traffic management computing device 12 extracts a client identification, such as one or more of a login 25 username, IP address, authentication credentials, and an authentication cookie value by way of example only, a session identification, and one or more values from the received user request, although other types and amounts of data can be

In step 110, the traffic management computing device 12 generates a monitoring request message, shown by way of example only as "asm_request.msg" in FIG. 3. The generated monitoring request message includes a timestamp and the extracted client identification, session identification, and one 35 or more values from the received user request, although other types of messages with other data may be generated. In step 112, the traffic management computing device 12 transmits the generated monitoring request to the database monitoring internal LAN provided by communication network 21(2), although other manners of transmitting this message over other types of connections and networks can be used. Once the monitoring request has been received by the database monitoring server 16, the database monitoring server 16 gen- 45 erates and transmits a monitoring acknowledgement response to the traffic management computing device 12.

In step 114, the traffic management computing device 12 receives the monitoring acknowledgement response, shown by way of example only as "dbm_ack.msg" in FIG. 3, from 50 the database monitoring server 16.

In step 116, the traffic management computing device transmits the received user request to the application server **18**. The application server **18** receives the user request forwarded from the traffic management computing device 12 55 and may issue one or more SQL requests for data or other operations from one or more of the data servers 20(1)-20(n), although other types and numbers of requests, such as an XML query, XPATH, or an WS security request by way of example only, to other types and numbers of devices could be 60 used. For illustration purposes in FIG. 3 for this particular example, the SQL requests from the application server 18 are provided to the data server 20(1), although the requests could be transmitted to other devices to obtain the requested data.

In step 118, with the information in the generated moni- 65 toring request, the database monitoring server 16 is now able to monitor and correlate data flows between the application

server 18 and one or more of the data servers 20(1)-20(n) which are associated with the received user request, although types of flows of requests and/or responses to other types of servers and computing devices could be monitored and correlated. The database monitoring server 16 also may apply one or more stored access or other policies to the data flows between the application server 18 and one or more of the data servers 20(1)-20(n), although the access or other policies could be applied to other types of flows to other types of servers and computing devices. Additionally, the database monitoring server 16 is able to generate an audit trail associate with the user request and the correlated SQL or other requests.

In step 120, the traffic management computing device 12 determines whether a response to the user request has been received. If in step 120, the traffic management computing device 12 determines a response to the user request has not been received, then the No branch is taken back to step 118 as described earlier and then database monitoring server 16 continues to monitor and correlate data flows between the application server 18 and one or more of the data servers 20(1)-20(n). If in step 120, the traffic management computing device 12 determines a response to the user request has been received, then the Yes branch is taken back to step 122.

In step 122, the traffic management computing device 12 generates and transmits a monitoring response message, shown by way of example only as "asm_response.msg" in FIG. 3, to the database monitoring server 16. When the database monitoring server 16 receives the monitoring response message it stops any further monitoring and correlation of data flows between the application server 18 and one or more of the data servers 20(1)-20(n) for the previously received user request. In step 124, the traffic management computing device 12 transmits the user response received from the application server 18 to the requesting one of the client computing devices 14(1)-14(n) which is shown by way of example only in FIG. 3 as client computing device 14(1) and then proceeds to step 104 as described earlier.

An exemplary method for identifying network traffic charserver 16 over an unencrypted TCP socket over a secure 40 acteristics to correlate and manage access to one or more subsequent flows will now be described with reference to FIGS. 1, 4 and 5. This exemplary method is the same as the exemplary method described with reference to FIGS. 1-3, except as illustrated and described herein. Steps in the exemplary method described with reference to FIGS. 1, 4, and 5 which are like those in the exemplary method described earlier with reference to FIGS. 1-3, will have like reference numerals and will not be described again.

In step 122, the traffic management computing device 12 generates and transmits a monitoring response message, shown by way of example only as asm_response. msg" in FIG. 3, to the database monitoring server 16. However, in this exemplary method the traffic management computing device 12 now waits for a subsequent action message from the database monitoring server 16 before determining what action to take with respect to the HTTP response to the received user request from one of the client computing devices 14(1)-14(n), which is shown by way of example only in FIG. 5 as client computing device 14(1). The database monitoring server 16 can monitor the data flows between the application server 18 and one or more of the data servers 20(1)-20(n) and generate one or more commands. In this example, the received action can comprise allowing this HTTP response to be transmitted to the requesting one of the client computing devices 14(1)-14(n), logging this HTTP response for auditing or other purposes in a memory storage device, reporting this HTTP response to one or more designated entities, quarantining or

otherwise blocking this HTTP response from being transmitted to the requesting one of the client computing devices 14(1)-14(n), if for example an SQL injection is detected, and terminating this HTTP response, although other types and numbers of operations based on a received command can be executed. The blocking may be at the web-application level, at the level of the transaction, or later for the user or user session and the commands may be based on the data access policy comprising one or more SQL injection policies in the database monitoring server 16.

In step 126, the traffic management computing device 12 determines whether an action message, shown by way of example only as "dbm_reply.msg" in FIG. 5, from the database monitoring server 16 has been received. If in step 126, the traffic management computing device 12 determines an action message from the database monitoring server 16 has not been received, then the No branch is taken back to the start of step 126, although other options are available, such as ending this method after a set period of time if a command message is not received. If in step 126, the traffic management computing device 12 determines an action message from the database monitoring server 16 has been received, then the Yes branch is taken to step 128.

In step 128, the traffic management computing device 12 executes the specified action in the message with respect to 25 the HTTP response to the received user request, although other types and numbers of operations can be performed. As noted earlier, these actions can, by way of example only, include allowing, logging, reporting, quarantining, or terminating the response to the received user request. Once the 30 traffic management computing device 12 has completed the action with respect to the HTTP response based on the received command, this exemplary method returns to step 104 as described earlier.

Accordingly, as illustrated and described in the exemplary methods herein, this technology provides effective methods, non-transitory computer readable medium, and devices that identify network traffic characteristics to correlate and manage one or more subsequent flows. With this technology, data access audit trails can be generated that are granular at the data level and also tie in attributes from the web application layer. Additionally, this technology can monitor and effectively alert or terminate a user session deemed to be misbehaving based on a data access policy. Further, this technology helps to secure both application and database environments from threats, such as SQL injection and cross-site scripting attacks.

Having thus described the basic concept of the invention, it will be rather apparent to those skilled in the art that the foregoing detailed disclosure is intended to be presented by 50 way of example only, and is not limiting. Various alterations, improvements, and modifications will occur and are intended to those skilled in the art, though not expressly stated herein. These alterations, improvements, and modifications are intended to be suggested hereby, and are within the spirit and 55 scope of the invention. Additionally, the recited order of processing elements or sequences, or the use of numbers, letters, or other designations therefore, is not intended to limit the claimed processes to any order except as may be specified in the claims. Accordingly, the invention is limited only by the 60 following claims and equivalents thereto.

What is claimed is:

1. A method for identifying network traffic characteristics to correlate and manage one or more subsequent flows executable by one or more traffic management devices with at 65 least one processor for executing the method, the method comprising:

8

transmitting, by a processor on the one or more traffic management devices, a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the HTTP request;

transmitting, by the processor on the one or more traffic management devices, the HTTP request to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server:

receiving, by the processor on the one or more traffic management devices, an HTTP response to the HTTP request from the application server;

transmitting, by the processor on the one or more traffic management devices, a monitoring response message to end the correlation associated with the HTTP request; and

performing, by the processor on the one or more traffic management devices, at least one operation with respect to the HTTP response when a command message in a response to the monitoring response message is not received before a predetermined period of time elapses.

2. The method of claim 1 wherein the performing further comprises:

outputting, by the processor on the one or more traffic management devices, the HTTP response to the requesting client computing device.

3. The method of claim 1 further comprising:

receiving, by the processor on the one or more traffic management devices, a determined action with respect to the HTTP request from the monitoring server which is based on at least one data access policy, wherein the performing further comprises executing, by the traffic management computing device, the determined action on the HTTP response.

- 4. The method of claim 3 wherein the determined action comprises one or more of allowing, logging, reporting, quarantining, and terminating, by the traffic management computing device, the output of the HTTP response to the requesting client computing device.
- **5**. The method of claim **1** wherein the one or more attributes comprise a client identification and a session identification in the HTTP request.
- **6**. The method of claim **5** wherein the one or more attributes further comprise one or more request values.
- 7. A non-transitory computer readable medium having stored thereon instructions for identifying network traffic characteristics to correlate and manage one or more subsequent flows comprising machine executable code which when executed by at least one processor, causes the processor to perform steps comprising:

transmitting a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the HTTP request;

transmitting the HTTP request to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server;

receiving an HTTP response to the HTTP request from the application server;

transmitting a monitoring response message to end the correlation associated with the HTTP request; and

performing at least one operation with respect to the HTTP response when a command message in a response to the

- monitoring response message is not received before a predetermined period of time elapses.
- **8**. The medium of claim **7** wherein the performing further comprises outputting the HTTP response to the requesting client computing device.
- **9**. The medium of claim **7** further comprising receiving a determined action with respect to the HTTP request from the monitoring server which is based on at least one data access policy, wherein the performing further comprises executing the determined action on the HTTP response.
- 10. The medium of claim 9 wherein the determined action comprises one or more of allowing, logging, reporting, quarantining, and terminating the output of the HTTP response to the requesting client computing device.
- 11. The medium of claim 7 wherein the one or more attributes comprise a client identification and a session identification in the HTTP request.
- 12. The medium of claim 11 wherein the one or more attributes further comprise one or more request values.
- 13. One or more traffic management computing devices comprising:

one or more processors;

- a memory coupled to the one or more processors which are configured to be capable of executing programmed instructions, which comprise the programmed instructions stored in the memory to:
- transmit a monitoring request comprising one or more attributes extracted from an HTTP request received from a client computing device and a timestamp to a monitoring server to correlate one or more subsequent flows associated with the HTTP request;

10

- transmit the HTTP request to an application server after receiving an acknowledgement response to the monitoring request from the monitoring server;
- receive an HTTP response to the HTTP request from the application server;
- transmit a monitoring response message to end the correlation associated with the HTTP request; and
- perform at least on operation with respect to the HTTP response when a command message in response to the monitoring response message is not received before a predetermined period of time elapses.
- 14. The device of claim 13 wherein the performing further comprises outputting the HTTP response to the requesting client computing device.
- 15. The device of claim 13 wherein the one or more processors is further configured to execute programmed instructions stored in the memory further comprising receiving a determined action with respect to the HTTP request from the monitoring server which is based on at least one data access policy, wherein the performing further comprises executing the determined action on the HTTP response.
- 16. The device of claim 15 wherein the determined action comprises one or more of allowing, logging, reporting, quarantining, or terminating the output of the HTTP response to the requesting client computing device.
- 17. The device of claim 13 wherein the one or more attributes comprise a client identification and a session identification in the HTTP request.
- **18**. The device of claim **17** wherein the one or more 30 attributes further comprise one or more request values.

* * * * *